

CBA Troughed belt conveyor

Composed of a fabricated profile section chassis, the **CBA conveyor is used for intensive industrial conveying.**

Its robust, stiff and flexible design endows it with great reliability and optimizes maintenance costs. Manufactured in our Sedan works.

Its ergonomics have been designed to meet legal requirements in terms of **personal safety, maintenance and service ability**, in compliance with current technical standards, in particular the **Machinery Directive 2006/42/EC**.

Common fields of use




Dry products



Wet products



Fine products



Products $\leq 1\,300\text{ kg/m}^3$



Recycling plants



Household waste



Industrial waste




Building/
Public Works



WEEE



ASR



Compost



Clinker




Usual fonctions

Transfer conveyor on length > 40 m • Dump trolley

Main characteristics

Standard belt widths	Length maxi	Linear speed	Belt conveyor
800 - 1 000 - 1 200 - 1 400 - 1 600 mm	≤ 100 m	≤ 2,00 m.s ⁻¹	Rubber band or PU Smooth or with battens or chevrons

Pre-equipment for options




Belt scraper




Shock absorber
rollers



Impact bars



Head and foot
drums covered
with anti-winding
discs creating
baffles to limit
material windings



Current cut

Advantages



Very reliable
industrial
equipment



Robust
design



Optimized
maintenance



Low energy
motor



High quality
components