

TBE Belt conveyor

Composed of a tubular profile chassis, the **TBE conveyor is used for intensive industrial conveying.**

Its clean, compact, stiff and flexible design endows it with great reliability and optimizes maintenance costs. Manufactured in our Sedan works.

Its ergonomics have been designed to meet legal requirements in terms of **personal safety, maintenance and service ability**, in compliance with current technical standards, in particular the **Machinery Directive 2006/42/EC**.

Common fields of use




Dry products



Wet products



Fine products



Products
≤ 250 kg/m³



Recycling plants



Household waste



Industrial waste




Building/
Public Works



WEEE



ASR



Compost



Usual fonctions

Transfer conveyor

Small and medium distance conveying

Lightweight products


Main characteristics

Standard belt widths	Length	Linear speed	Belt conveyor
600 - 800- 1 000 - 1 200 1 400 - 1 600 mm	≤ 40 m maxi	≤ 2,00 m.s ⁻¹	Rubber band, PVC or PU Smooth, with cleats or rafters


Pre-equipment for options




Stone catcher



Belt scraper



Impact bars and shock absorber rolls



Mud flaps

Sorting separator also included

Advantages



Very reliable industrial equipment



Robust design




Optimized maintenance



Low energy motor



High quality components



Height adjustable equipment